

NATURAL RESOURCES CONSERVATION SERVICE
VIRGINIA CONSERVATION PRACTICE STANDARD

PIPELINE

(Feet)

CODE 516

DEFINITION

Pipeline having an inside diameter of 8 inches or less.

PURPOSE

To convey water from a source of supply to points of use for livestock, wildlife, or other agricultural purposes.

CONDITIONS WHERE PRACTICE APPLIES

Where it is desirable or necessary to convey water in a closed conduit from one point to another.

CRITERIA

CAPACITY

For livestock water, the installation shall have a capacity to provide seasonal high daily water requirements for the number and species of animals to be supplied. Animal water requirements can be obtained from the NRCS, Virginia Field Office Technical Guide, Section IV.

Additional water capacity will be provided for wildlife when applicable.

PIPE

All pipe must withstand the pressure it will be subjected to, including hydraulic transients, internal pressures, and external pressures. As a safety factor against surge or water hammer, the working pressure should not exceed 72% of the pressure rating of the pipe and the design flow velocity at system capacity should not exceed 5 ft/sec (1.5 m/s). If either of these limits is exceeded, special consideration must be given to flow conditions and measures must be taken to adequately protect the pipeline against surge.

Steel pipe shall meet the requirements of AWWA Specification C-200.

Plastic pipe shall conform to the requirements of the following ASTM specifications, as applicable:

D 1527 Acrylonitrile-Butadiene-Styrene (ABS) Plastic Pipe, Schedules 40 and 80

D 1785 Poly (Vinyl Chloride) (PVC) Plastic Pipe, Schedules 40, 80, and 120

D 2104 Polyethylene (PE) Plastic Pipe, Schedule 40

D 2239 Polyethylene (PE) Plastic Pipe (SIDR-PR) Based on Controlled Inside Diameter

D 2241 Poly (Vinyl Chloride) (PVC), Pressure-Rated Pipe (SDR Series)

D 2282 Acrylonitrile-Butadiene-Styrene (ABS) Plastic Pipe (SDR-PR)

D 2447 Polyethylene (PE) Plastic Pipe Schedules 40 and 80, Based on Outside Diameter

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.

516-VA-2

D 2672 Joints for IPS PVC Using Solvent Cement

D 2737 Polyethylene (PE) Plastic Tubing

D 3035 Polyethylene (PE) Plastic Pipe (SDR-PR)
Based on Controlled Outside Diameter

AWWA C900 Polyvinyl Chloride (PVC) Pressure
Pipe, 4 inches through 12 inches

AWWA C901 Polyethylene (PE) Pressure Pipe and
Tubing, ½ inch through 3 inches

Plastic pressure pipe fittings shall conform to the
following ASTM specifications, as applicable:

D 2464 Threaded Poly (Vinyl Chloride) (PVC)
Plastic Pipe Fittings, Schedule 80

D 2466 Poly (Vinyl Chloride) (PVC) Plastic Pipe
Fittings, Schedule 40

D 2467 Socket-Type Poly (Vinyl Chloride) (PVC)
Plastic Pipe Fittings, Schedule 80

D 2468 Acrylonitrile-Butadiene-Styrene (ABS)
Plastic Pipe Fittings, Schedule 40

D 2609 Plastic Insert Fittings for Polyethylene (PE)
Plastic Pipe

D 2683 Socket-type Polyethylene Fittings for
Outside Diameter-Controlled Polyethylene Pipe and
Tubing

D 3139 Joints for Plastic Pressure Pipes Using
Flexible Elastomeric Seals

D 3261 Butt Heat Fusion Polyethylene (PE) Plastic
Fittings for Polyethylene (PE) Plastic Pipe and
Tubing

Solvents for solvent-welded plastic pipe joints shall
conform to the following ASTM specifications, as
applicable:

D 2235 Solvent Cement for Acrylonitrile- Butadiene-
Styrene (ABS) Plastic Pipe and Fittings

D 2564 Solvent Cements for Poly (Vinyl Chloride)
(PVC) Plastic Pipe and Fittings

D 2855 Standard Practice for Making Solvent-
Cemented Joints with Poly (Vinyl Chloride) (PVC)
Pipe and Fittings

Rubber gaskets for pipe joints shall conform to the
requirements of ASTM Specification
F 477, Elastomeric Seals (Gaskets) for Joining
Plastic Pipe.

DRAINAGE

Valves or unions shall be installed at low points in the pipeline so that the line can be drained as needed. Check valves shall be installed as needed to protect groundwater quality or maintain a full pipeline.

VENTS

Design shall provide for entry and removal of air along the pipeline, as needed, to prevent air locking or pipe collapse. If parts of the line are above the hydraulic gradient, periodic use of an air pump may be required. Provisions shall be made for pressure relief, air relief, and vacuum relief as needed to protect the pipeline.

JOINTS

Watertight joints that have a strength equal to that of the pipe shall be used. Couplings must be of material compatible with that of the pipe. If they are made of material susceptible to corrosion, provisions must be made to protect them.

PROTECTION

When steel pipe is used, interior protective coatings shall be provided in accordance with NRCS Virginia Conservation Practice Standard *Irrigation Pipeline (Code 430)*. If a coal-tar enamel protective coating is needed for corrosion protection, the coating shall meet the requirements of AWWA Specification C-203.

Steel pipe installed above ground shall be galvanized or shall be protected with a suitable protective paint coating, including a primer coat and two or more final coats.

Plastic pipe installed above ground shall be resistant to ultraviolet light throughout the intended life of the pipe.

All pipes shall be protected from hazards presented by traffic, farm operations, freezing temperatures, fire, and thermal expansion and contraction. Reasonable measures should be taken to protect the pipe from potential vandalism.

VEGETATION

Disturbed areas shall be established with vegetation or otherwise stabilized as soon as practical after construction. Seedbed preparation, seeding, fertilizing, and mulching shall conform to NRCS Virginia Conservation Practice Standard *Critical Area Planting (Code 342)*.

VISUAL RESOURCES

The visual design of pipelines and appurtenances in areas of high public visibility shall be carefully considered.

CONSIDERATIONS

No special considerations have been identified for this practice.

PLANS AND SPECIFICATIONS

Plans and specifications for installing pipelines shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose. If the pipeline is a component of a system that includes additional conservation practices, the information necessary to construct these additional practices will also be conveyed on the plans.

The Engineering Field Handbook, Chapter 5, will guide the development of plans.

DESIGN DATA

1. Record all design data in an engineering field book, and/or on a plan, or on a design sheet.
2. Estimate the rate of water required.
3. Estimate the rate of water supply.
4. If a pressure system, determine the needed pressure range in psi.
5. Profile along proposed line from source to point of delivery. Profile of outlet pipe.

516-VA-4

6. Detail profile/plan by sections, type, ASTMs, length, sizes, and depths of pipe.
7. Basis for pipe sizes selected.
8. Completed Environmental Evaluation.

Compliance with NEPA.

3. Midwest Plan Service, Structures and Environment Handbook: MWPS-1.

CHECK DATA

1. Record all check data in an engineering field book, and/or on a plan, or on a design sheet.
2. Document length, depth, size and type of pipe used.
3. A statement as to seeding, sodding, or successful establishment of vegetation.
4. A statement that the pipeline was pressure tested for leaks prior to backfill.

OPERATION AND MAINTENANCE

Operation and Maintenance requirements specific to the type of installed pipeline shall be provided to the landowner. The plan shall include, but not be limited to, the following provisions:

- Opening/closing valves to prevent excessive water hammer
- Filling at the specified rate requirements
- Inspecting and testing valves, pressure regulators, pumps, switches and other appurtenances
- Maintaining erosion protection at outlets
- Checking for debris, minerals, algae and other materials which may restrict system flow
- Draining and/or providing for cold weather operation of the system

REFERENCES

1. National Engineering Handbook, Part 650, Engineering Field Handbook.
2. GM-190, ECOL SCI, Part 410,

NATURAL RESOURCES CONSERVATION SERVICE
VIRGINIA CONSERVATION PRACTICE STANDARD
PIPELINE

Approved Practice Narratives

(Feet)

CODE 516

516 D1 Pipeline: A pipeline to supply water for livestock will be installed at the location shown on the plan map.

516 D2 Pipeline: A pipeline to supply water for wildlife shall be installed at the location shown on the plan map.

516 D3 Pipeline: A pipeline to supply water for agricultural use shall be installed at the location shown on the plan map.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, sex, religion, age, disability, political beliefs, sexual orientation, or marital or familial status. (Not all prohibited bases apply to all programs.) Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD.)

582-VA-6

To file a complaint of discrimination, write USDA, Director, Office of Civil Rights, Room 326W, Whitten Building, 14th and Independence Avenue, SW, Washington, DC, 20250-9410 or call (202) 720-5964 (voice and TDD.) USDA is an equal opportunity provider and employer.